

FUJI

 GENROSE







9"x40" Field Tile in Mayo



9"x40" Field Tile in Atlin



## AVAILABLE IN:


















9.5mm Field Tiles		
SIZE	FINISH	COLORS
9"x40"	Matte	Klondike   Watson   Atlin   Mayo

## MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES	BASKETWEAVE
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		
			
<b>FIELD SHAPES*</b>		<b>CHEVRONS</b>	<b>HERRINGBONE</b>
 Half Hexagon	6.7" Base		
 Diamond	4"		
 Hexagon	6"		
 Chevron	2"x12" 6"x24"	2" w/ 0.6" Squares	1 1/8" 2"
<b>TRAPEZOID W/ DOT</b>	<b>SQUARES</b>	<b>RECTANGLES</b>	
	4"x2 1/2" w/ 5/8" Dot	1"x1"    2"x2" 1 3/8"x1 3/8"    3"x3"	1"x2" 1"x4"

\*Other sizes available upon request

All Sizes are Nominal.



Klondike



Watson



Atlin



Mayo

Colors shown may vary from actual product. Final selection should be made from actual product samples.





9"x40" Field Tile in Klondike

Features	Test Method	Value
Sides	EN ISO 10545 - 2	± 0.9mm
Thickness		± 0.5mm
Straightness of Sides		± 0.75mm
Rectangularity		
Surface Flatness		
Water Absorption	EN ISO 10545 - 3	≤ 0.1%
Flexion Resistance	EN ISO 10545 - 4	S ≥ 1.300 N R ≥ 35 N/mm <sup>2</sup>
Impact Resistance	EN ISO 10545 - 5	> 0.80
Coefficient of Linear Thermal-Expansion	EN ISO 10545 - 8	a = 6.7 x 10 <sup>-6</sup> / C°
Resistance to Thermal Shock	EN ISO 10545 - 9	Resistant
Moisture Expansion	EN ISO 10545 - 10	MAX 0.1mm/m
Frost Resistance	EN ISO 10545 - 12	Resistant
Resistance to Household and Swimming Pool Chemical Products	EN ISO 10545 - 13	B MIN
Resistance to Stains	EN ISO 10545 - 14	Class 3 Min
Lead and Cadmium Discharge	EN ISO 10545 - 15	< Than Instrument Limit
DCOF	DM. 236/89 BCRA	> 0.40
	ANSI A 137.1	> 0.42
	DIN 51130	R10
	DIN 51097	A+B



This product will contribute to USGBC registered LEED projects.  
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.  
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9.5mm Thicknesses
- Pressed Edge
- PEI Rating = 5
- Frost Resistance = Yes



**V4 - EXTREME** variation is inherent in this tile.  
All material must be inspected prior to installation.  
Absolutely no claims will be accepted after installation.



[www.genrose.com](http://www.genrose.com)

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.





[www.genrose.com](http://www.genrose.com)