

SHADOW

 GENROSE





2.5"x5" Wall Tile in Grey



2.5"x5" Wall Tile in Aqua



2.5"x5" Wall Tile in Steel



2.5"x5" Wall Tile in Copper



2.5"x5" Wall Tile in Graphite



2.5"x5" Wall Tile in Emerald

AVAILABLE IN:

10mm Wall Tiles

Pressed Edge

2.5"x5" Matte | Glossy Finish

Trim Pieces

1.5"x5" Bullnose Matte | Glossy Finish



- All sizes are NOMINAL

- Steel and Copper are only available in 2.5"x5" Wall Tile in Glossy



2.5"x5" Wall Tile in Mustard

WALL TILE COLORS:



White



Warm



Grey



Graphite



Steel (Glossy Only)



Copper (Glossy Only)



Aqua



Mint



Mustard



Ocean



Emerald


Colors shown may vary from actual product. Final selection should be made from actual product samples.

WALL TILE COLOR VARIATION:


*Different shades randomly mixed within the box.




White



Graphite




Aqua



Ocean



Warm



Mint



Emerald



Grey



Mustard

Features	Test Method	Value
Dimensional Features	ISO 10545-2	62 mm +/- 0.75 mm x 125 mm +/- 0.75 mm
Water Absorption	ISO 10545-3	$E_b \leq 10\%$
Modulus of Rupture	ISO 10545-4	Thickness ≥ 7.5 mm Min 12 N/mm ² Thickness < 7.5 mm Min 15 N/mm ²
Crazing Resistance	ISO 10545-11	Resistant
Household Chemical Resistance	ISO 10545-13	GA
Chemical Resistance	ISO 10545-13	GHA (except for Steel and Copper)
Stain Resistance	ISO 10545-14	5

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Tile
- Matte | Glossy Finish
- 10mm Thickness
- Pressed Edge
- V4 - Substantial Variation
- Frost Resistance = No





www.genrose.com