



Features	Test Method	Value	
		Rectified	Calibrated
Warpage	ASTM C485	± 0.40%	± 0.50%
Wedging	ASTM C502	± 0.25%	± 0.50%
Thickness	ASTM C499	≤0.04 in	
Water Absorption	ASTM C373	≤0.4%	
Surface Wear Resistance	ANSI A137.1	All Residential/Commercial	
Breaking Strength	ASTM C648	10mm ≥400 lbf	
Chemical Resistance	ASTM C650	Not affected	
Frost Resistance	ASTM C1026	Resistant	
Stain Resistance	ASTM C1378	Resistant	
DCOF (WET)	ANSI A326.3	≥0.42 WET	
Recycled Material	-	≥45%	

This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- Frost Resistance = Yes



www.genrose.com