

Features	Test Method	Value	
Length / Width	EN ISO 10545 - 2	± 0.25%	
Thickness		± 2.5%	
Straightness of Side		± 0.15%	
Rectangularity		± 0.4%	
Surface Flatness		± 0.2%	
Water Absorption		EN ISO 10545 - 3	15% to 17%
Weight / M ²	-	8mm Thick	10mm Thick
		14.85 kg	17.78 kg
Modulus of Rupture	EN ISO 10545 - 4	≥ 25 N / mm ²	
Thermal Shock	EN ISO 10545 - 9	Pass	
Frost Resistance	EN ISO 10545 - 12	Not Suitable	
Chemical Resistance	EN ISO 10545 - 13	Class A - B	
Stain Resistance	EN ISO 10545 - 14	Class 3	
Fire Rating	-	Class A1 Non Combustible	
Recycled Content	-	Up to 20%	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.


Product Info:

- Ceramic Tile
- 8mm | 10mm Thicknesses
- Gloss | Satin Finishes
- V1 - Uniform Appearance
- Frost Resistance = No


www.genrose.com