



Features	Test Method	Value	
		8.5mm	20mm
Water Absorption	ISO 10545-3	~ 0.1%	~ 0.1%
Bending Strength	ISO 10545-4	~ 50 N/mm ²	~ 50 N/mm ²
Breaking Strength	ISO 10545-4	> 1300 N	> 1300 N
Impact Resistance	ISO 10545-5	~ 0.89 (COR)	~ 0.89 (COR)
DEEP Abrasion	ISO 10545-6	135 mm ³ Mohs ≥6	135 mm ³ Mohs ≥6
Linear Thermal Expansion	ISO 10545-8	~ 6.4x10 ⁻⁶ °C ⁻¹	~ 6.4x10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	ISO 10545-9	Resistant	Resistant
Frost Resistance	ISO 10545-12	Resistant	Resistant
Chemical Resistance	ISO 10545-13	GB	GA
Stain Resistance	ISO 10545-14	Class 3	Class 3
Color Resistance to Light Exposure	DIN 51094	Resistant	Resistant
Breakage Load	EN 12825	-	Class 1
Mechanical Strength	EN 1339-F	-	U11
Slip Resistance	DIN 51130	Natural: R10 Grip: R11	R11
	DIN 51097	Natural: B Grip: C	C
	ANSI A 326.3:2019 release 2019 (DCOF)	Natural: 0.66 Grip: 0.88	0.70

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural Finish
- 8.5mm | 20mm Thicknesses
- Rectified | Pressed Edges
- V3 - Moderate Variation
- Frost Resistance = Yes