

Features	Test Method	Value		
Length and Width	ISO 10545-2	± 0.3 %		
Thickness	ISO 10545-2	10 ± 3.0 %		
Straightness of Sides	ISO 10545-2	± 0.3 %		
Rectangularity	ISO 10545-2	± 0.3 %		
Surface Flatness	ISO 10545-2	± 0.2 %		
Water Absorption	ISO 10545-3	≤ 0.5%		
Breaking Strength	ISO 10545-4	>1300 N		
Modulus of Rupture	ISO 10545-4	>35 N/mm <sup>2</sup>		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Crazing Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Coefficient of Friction	-	R10		
Chemical Resistance	ISO 10545-13	Household	Low Conc.	High Conc.
		GA	GLA	GHA
Resistance to Stains	ISO 10545-14	5		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matt Finish
- 10mm Thickness
- Pressed Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

