

Features	Test Method	Value
Sides	EN ISO 10545 - 2	± 0.9mm
Thickness		± 0.5mm
Straighness of Sides		± 0.75mm
Rectangularity		
Surface Flatness		
Water Absorption	EN ISO 10545 - 3	≤ 0.1%
Flexion Resistance	EN ISO 10545 - 4	S ≥ 1.300 N R ≥ 35 N/mm ²
Impact Resistance	EN ISO 10545 - 5	> 0.80
Coefficient of Linear Thermal-Expansion	EN ISO 10545 - 8	a = 6.7 x 10 ⁻⁶ / C°
Resistance to Thermal Shock	EN ISO 10545 - 9	Resistant
Moisture Expansion	EN ISO 10545 - 10	MAX 0.1mm/m
Frost Resistance	EN ISO 10545 - 12	Resistant
Resistance to Household and Swimming Pool Chemical Products	EN ISO 10545 - 13	B MIN
Resistance to Stains	EN ISO 10545 - 14	Class 3 Min
Lead and Cadmium Discharge	EN ISO 10545 - 15	< Than Instrument Limit
DCOF	DM. 236/89 BCRA	> 0.40
	ANSI A 137.1	> 0.42
	DIN 51130	R10
	DIN 51097	A+B



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 9.5mm Thicknesses
- Pressed Edge
- PEI Rating = 5
- Frost Resistance = Yes



V4 - EXTREME variation is inherent in this tile.
All material must be inspected prior to installation.
Absolutely no claims will be accepted after installation.



www.genrose.com