

Features	Test Method	Value
Flatness	ISO 10545-2	± 0.26 % ± 1.5 mm
Water Absorption	ISO 10545-3	Compliant
Modulus Of Rupture	ISO 10545-4	≥50 N/mm ²
Breaking Strength	ISO 10545-4	≥2000 N
Frost Resistance	ISO 10545-12	Compliant
Chemical Resistance	ISO 10545-13	GA - GLA - GHA
Stain Resistance	ISO 10545-14	5
Slip Resistance	ANSI A 137.1 - 2012 DCOF (Section 9.6)	WET≥0.42
Recycled Material	-	Min. 7.5%
This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Glazed Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 4 (Grey | Mud | Dark)
5 (White)
- V3 - Moderate Variation
- Frost Resistance = Yes


www.genrose.com