



Features	Test Method	Value
Thickness	ASTM C499	≤ 0.05"
Wedging	ASTM C502	Min. -1.0% Max. 1.0%
Warpage	ASTM C485	Min. -1.5% Max. 1.5% along any edge. Min -1.0% Max 1.0% on either diagonal.
Water Absorption	ASTM C373	0.3% max.
Bond Strength	ASTM C482	≥ 50 P.S.I
Abrasion Resistance	ASTM C1243	< 275 mm ³
Scratch Hardness	Mohs	7 Mohs
Breaking Strength	ASTM C648	800 lbf
Chemical Resistance	ASTM C650	Class A
Frost Resistance	ASTM C1026	Resistant
Stain Resistance	ASTM C1378	Meets the standard.
DCOF (WET)	ANSI A326.3	≥ 0.60
Recycled Material	-	≤23% (#57IS Puritan Gray) ≤18% (#31IS Mayflower Red)
  LEED V4 <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Quarry Tile
- Smooth Finish
- Relieved Edge
- 12.7mm Thickness
- Frost Resistance = Yes
- V1 - Uniform Appearance
- Application = Heavy Commercial Use



www.genrose.com