




Features	Test Method	Value	
Thickness	ISO 10545 - 2	12" x 24" - 8.5mm	40" x 40" - 10mm
		± 0.5mm	± 0.5mm
Straightness of Sides		±1.2mm	± 1.0mm
Rectangularity		± 1.5mm	± 1.5mm
Surface Flatness		± 1.2mm	± 1.5mm
Surface Quality		95%	95%
Warpage		± 1.2mm	± 1.5mm
Water Absorption		ISO 10545 - 3	E ≤ 0.5%
Modulus of Rupture	ISO 10545 - 4	> 35 N/mm ²	
Breaking Strength		≥ 1300 N	
Surface Hardness (Mohs)	UNE 67101:1985	7	
Surface Abrasion Resistance	ISO 10545 - 8	Class 4	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance (Domestic)	ISO 10545-13	A	
Chemical Resistance (Low Concentration)		LA	
Chemical Resistance (High Concentration)		HA	
Stain Resistance	ISO 10545-14	Min. Class 4	
Slip Resistance DCOF (WET)	ANSI A137.1	R10 ≥ 0.50	
Recycled Material	-	29%	

This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 8.5mm | 10mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes
- Application = Residential and Commercial



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.