

Technical Characteristics	Test Method	Porcelain Fixed Value	Wall Tile Fixed Value
Thickness	ISO 10545-2	± 5 % (0.48 mm)	± 10 % (0.50 mm)
Length And Width		± 0.6% (2 mm)	± 0,50 % (2 mm)
Squareness		± 0.50 % (2 mm)	± 0.50 % (2 mm)
Straightness Of Sides		± 0.50 % (1.5 mm)	± 0.30 % (1.5 mm)
Surface Flatness		± 0.5% (2 mm)	± 0.3% / +0.5% (-1.50 mm / +2.00mm)
Fixing	UNE CEN/TR 13548 IN	Interior: >= 3mm Exterior: >= 5mm.	Interior: >= 3mm Exterior: none
Breaking Strength	ISO 10545-4	1300 N	600 N
Modulus Of Rupture		35 N/mm ²	12 N/mm ²
Resistance to Abrasion	ISO 10545-6	130 mm ³	NPD
Resistance to Chemicals		UA/ULA/UHA	GA/GLA/GHA
Resistance to Staining	ISO 10545-14	Class 5	Class 5
Slip Potential-Wet	UNE-ENV 12633	Base- High Antislip-Low	-
Slip Potential-Dry	UNE-ENV 12633	Base- Low Antislip-Low	-

Product Info:

- Porcelain Tile
- Contact your sales representative for more information



V4 - Substantial variation is inherent in this tile.
All material must be inspected prior to installation.
Absolutely no claims will be accepted after installation.

