


Features	Value	
Thickness	3.5mm	10mm
Water Absorption	≤ 0.1%	≤ 0.5%
Exterior Rated	Yes	-
DCOF AcuTest	Fail	Pass
Glaze Hardness	7 mohs	7 mohs
Breaking Strength	≥250 lbf	≥510 lbf
Durability Classification	IV Commercial	Residential, Light Commercial & Heavy Commercial
Deep Abrasion	P1	-
Recycled Material	≥40%	≥40%
 <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 10mm | 3.5mm Thicknesses
- Rectified Edge
- PEI Rating = 2 - Ask | Eclipse | Nut | Velvet
3 - Titanium
4 - Cotton
- Frost Resistance = Yes
- V2 - Slight Shading Variation



www.genrose.com