

Features	Test Method	Value
Water Absorption	ASTM C373	≤ 0.5
Breaking Strength	ASTM C648	350 lbf 9 mm
Deep Abrasion Resistance	ASTM C1243	145 mm ³
Linear Thermal Expansion	ASTM C372	≤ 4.4 x 10 ⁻⁶ °F-1 ≤ 8x 10 ⁻⁶ °C-1
Stain Resistance	ASTM C1378	A Resistant
Chemical Resistance	ASTM C650	A Resistant
Frost Resistance	ASTM C1026	Resistant
Bond Strength	ASTM C482	≥ 50 PSI
Flame Spread	ASTM E84	Class A
Thermal Conductivity	EN 12524	= 1,3 W/m °K / 0.7 BTU/ft h °F
DCOF (WET)	ANSI A326.3	≥ 0.42
Recycled Material	-	40%



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC



This product has a permanent Microban treatment on the surface to reduce the growth of mold, mildew, and bacteria. The antimicrobial technologies from Microban do not need to be reapplied or activated and are registered with the Environmental Protection Agency (EPA) in the US and comply with the standards of the Biocidal Products Regulation (BPR) in Europe.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Note:

- This collection is suitable for Light Commercial

Product Info:

- Color Body Porcelain Tile
- Soft Finish
- 9mm Thickness
- Rectified Edge
- V3 - Moderate Shading Variation (Imperiale Grey | Onice Cream)
- V4 - Extreme Shading Variation (Travertino White | Calacatta Gold)
- Frost Resistance = Yes



www.genrose.com