

Features	Test Method	Value	
		9mm	20mm
Surface Quality	ISO 10545-2	Min. 95% of tiles without defects	
Water Absorption	ISO 10545-3	E < 0.5 %	
Bending Strength	ISO 10545-4	> 52 N/mm ²	> 35 N/mm ²
Breaking Strength	ISO 10545-4	> 2500 N	> 1300 N
Resistance to Deep Abrasion	ISO 10545-6	(Natural and Anti-Slip Finish)	(Anti-Slip Finish)
		<109 mm ³	<175 mm ³
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Resistance of Chemical Attack Low Concentration	ISO 10545-13	GLA/GHA	
Resistance of Chemical Attack Domestic Chemicals		GA	
Stain Resistance	ISO 10545-14	Class 5	
Slip Resistance	UNE ENV 12633	Class 1 Matte Class 3 Anti-Slip	Class 3 Anti-Slip
Reaction to Fire	UNE EN 13501-1:2002	A1/A1FL	
DCOF	ANSI A326.3:2017	0.62 - Matte 0.93 - Anti-Slip	
Recycled Content	-	≥ 30%	
    <p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70. Zero VOC</p>			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.




Product Info:

- Color Body Porcelain Tile
- Matte | Anti-Slip Finishes
- 6mm | 9mm | 20mm Thicknesses
- Rectified Edge
- PEI Rating = 3
- V2 - Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com

Features	Test Method	Value	
		6mm	11mm
Surface Quality	ISO 10545-2	Min. 95% of tiles without defects	
Water Absorption	ISO 10545-3	E > 10%	
Bending Strength	ISO 10545-4	> 20 N/mm ²	> 15 N/mm ²
Breaking Strength	ISO 10545-4	> 400 N	> 600 N
Crazing Resistance	ISO 10545-11	Resistant	
Resistance of Chemical Attack	ISO 10545-13	Low Concentration	
		GLA	GLA/GHA
		Domestic Chemicals	
		GA	GA
Stain Resistance	ISO 10545-14	Class 5	
Reaction to Fire	UNE EN 13501-1:2002	A1/A1FL	
Recycled Content	-	≥ 30%	

  	<p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70. Zero VOC</p>
---	---

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Product Info:

- Ceramic Tile
- Matte Finish
- 9mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = No