

CHATHAM



For the most up-to-date product information, scan the QR code.code.





12" x 48" | 8" x 48" Field Tile in Acero
24" x 48" Field Deco in Acero



12" x 48" | 8" x 48" Field Tile in Rovere

AVAILABLE STOCKED ITEMS:

10mm Field Tile - Rectified Edge		
SIZE	FINISH	COLORS
8" x 48"	Matte	Rovere Acero Noce
10mm Field Deco - Rectified Edge		
SIZE	FINISH	COLORS
24" x 48"	Matte	Rovere Acero Noce

AVAILABLE SPECIAL ORDER ITEMS:

10mm Field Tile - Rectified Edge		
SIZE	FINISH	COLORS
12" x 48"	Matte	Rovere Acero Noce

All Sizes are Nominal.

8" X 48" FIELD TILE:



Rovere Acero Noce

12" X 48" FIELD TILE:



Rovere Acero Noce



Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

24" X 48" FIELD DECO:



Rovere



Acero




Noce



12" x 48" | 8" x 48" Field Tile in Noce

Features	Test Method	Value
Length and Width	ISO 10545-2	±2.0 mm
Thickness		±0.5 mm
Straightness of Sides		Compliant
Rectangularity		±1.5 mm
Surface Flatness		Compliant
Surface Quality		Compliant
Warpage		±2.0 mm
Wedging		±2.0 mm
Water Absorption		Eb < 0.5%
Modulus of Rupture / Bending Strength		ISO 10545-3
Breaking Strength	ISO 10545-4	≥ 1300 N
Surface Hardness (Mohs)	UNI EN - 101	7
Resistance to Surface Abrasion	ISO 10545-6	< 150 MM ³
Coefficient of Linear Thermal Expansion	ISO 10545-8	< 9MK-1
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance (Domestic)	ISO 10545-13	UA
Chemical Resistance (Low Concentration)		ULA-ULB
Chemical Resistance (High Concentration)		UHA-UHB
Stain Resistance	ISO 10545-14	Class 5
Slip Resistance	ANSI A326.3:2021	DCOF = 0.52
Recycled Content	-	≥20%



This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
 Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes





www.genrose.com