HEARTH







48" x 48" Floor/Wall Tile in Cloud 24" x 48" Floor/Wall Tile in Jade



24" x 48" Floor/Wall Tile in Iron 48" x 110" 6mm Slab in Dark



48" x 48" Floor/Wall Tile in Ice 48" x 110" Slab in Ice





24" x 48" Floor/Wall Tile in Iron 32" x 32" Outdoor Paver in Iron

AVAILABLE STOCKED ITEMS:

9mm Floor/Wall 1	Tiles - Rectified Ed	ge			
SIZE	FINISH		COLORS		
3" × 12"	Matte		Ice Cloud Jade Iron Dark		
12" x 24"	Matte		Ice Cloud Jade Iron Dark		
9mm Floor/Wall I	Mosaics - Rectified	Edge			
SHEET SIZE	ТҮРЕ	FINISH	COLORS		
12" x 12"	2" x 2" Mosaic	Matte	Ice Cloud Jade Iron Dark		

SPECIAL ORDER ITEMS:

9mm Floor/Wall T	iles - Rectified Ed	ge			
SIZE	FINISH		COLORS		
24" x 24"	Matte		Ice Cloud Jade Iron Dark		
24" × 24"	Grip		Cloud Iron		
32" x 32"	Matte		Ice Iron Dark		
24" x 48"	Matte		Ice Cloud Jade Iron Dark		
48" × 48"	Matte		Ice Cloud Jade Iron Dark		
9mm Floor/Wall N	Mosaics - Rectified	l Edge			
SHEET SIZE	TYPE	FINISH	COLORS		
12.6" x 21.26"	Picket Mosaic	Matte	Ice Cloud Jade Iron Dark		
20mm - Outdoor I	Pavers - Rectified	Edge			
SIZE	FINISH		COLORS		
24" × 24"	Grip		Iron		
32" x 32"	Grip		Iron		
18" x 36"	Grip		Iron		
24" × 48"	Grip		Iron		
6mm Slab - Recti	fied Edge				
SIZE	FINISH		COLORS		
48" x 110"	Matte		Ice Dark		

All Sizes are Nominal.







Jade



Dark



Cloud




Iron


Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.





2" x 2" MOSAIC











PICKET MOSAIC











MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1³/ ₈ ″x3″ 2″x4″
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4"
Diamond	4"			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	⁵ / ₈ "x4"
		OCTAGONS		HEXAGONS	
— Hexagon	6"		2"		***
Chevron	2"×12" 6"×24"		2" w/ 0.6" Squares		1¹/8″ 2″
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

^{*}Other sizes available upon request





Features	Test Method	Value	
Length and Width		Conforms	
Thickness	100 107 17 0	9mm	
Straightness of Sides	ISO 10545-2	Rectified	
Surface Flatness		Compliant	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C502	Compliant	
Water Absorption	ISO 10545-3	≤ 0.1%	
Modulus of Rupture / Bending Strength	ISO 10545-4	54.6	
Breaking Strength	ISO 10545-4	2094	
Abrasion Resistance	ISO 10545-6	Conforms	
Coefficient of Linear Thermal Expansion	ISO 10545-8	~ 7 (10 ⁻⁶ °C ⁻¹)	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Expansion in Humidity	ISO 10545-10	≤ 0.1 (mm/m)	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance (Low Concentration)	ISO 10545-13	Resistant	
Stain Resistance	ISO 10545-14	Cleanable	
D.C.O.F. (WET) Slip Resistance	ANSI A326.3	0.69	
Recycled Material	-	Cloud Jade Iron Dark = 20%	
VOC Emissions	-	Low Emissions Material - Zero VOC	

It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Tile
- Matte Finish
- 6mm | 9mm | 20mm Thicknesses
- Rectified Edge
- V2 Moderate Variation
- Frost Resistance = Yes







www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com