

OSLO

 GENROSE



For more product information, scan the QR code.





12" x 36" Wall Deco in Light
12" x 36" Wall Tile in Light
36" x 36" Floor/Wall Tile in Light

AVAILABLE STOCKED ITEMS:

10.5mm Field Tiles		
SIZE	FINISH	COLORS
36" x 36"	Matte	Light Base
10.5mm Wall Tiles		
SIZE	FINISH	COLORS
12" x 36"	Matte	Light Base
10.5mm Wall Decos		
SIZE	FINISH	COLORS
12" x 36"	Matte	Light Base




















All Sizes are Nominal.

MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES	BASKETWEAVE
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		
			
FIELD SHAPES*		CHEVRONS	HERRINGBONE
	Half Hexagon		
	6.7" Base		
	Diamond		
	4"		
	Hexagon		
	6"		
	Chevron		
	2"x12" 6"x24"		
TRAPEZOID W/ DOT		SQUARES	RECTANGLES
	4"x2 1/2" w/ 5/8" Dot		
		1"x1" 2"x2" 1 3/8"x1 3/8" 3"x3"	1"x2" 1"x4"

*Other sizes available upon request



Light Wall Tile - V1 



Light Wall Deco - V1 



Light Field Tile - V2 



Base Wall Tile - V1 





Base Wall Deco - V1 





Base Field Tile - V2 

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

Features	Test Method	Value
Dimensions and Surface Quality	ISO 10545-2	Compliant
Water Absorption	ISO 10545-3	16%
Breaking Strength	ISO 10545-4	600 - 900 N
Modulus of Rupture	ISO 10545-4	15 – 25 N/mm ²
Thermal Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Chemical Resistance	ISO 10545-13	Alkaline - Class A
		Acid - Compliant
Stain Resistance	ISO 10545-14	Class 5
Recycled Material	-	≥29%
  <p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Features	Test Method	Value
Dimensions and Surface Quality	ISO 10545-2	Compliant
Water Absorption	ISO 10545-3	≤ 0.5
Breaking Strength	ISO 10545-4	1,600 - 2,400 N
Modulus of Rupture	ISO 10545-4	35 – 45 N/mm ²
Thermal Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Chemical Resistance	ISO 10545-13	Alkaline - Class A
		Acid - Compliant
Stain Resistance	ISO 10545-14	Class 5
DCOF (WET)	ANSI B101.3	Base - 0.48 Light - 0.59
Recycled Material	-	≥31%
  <p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Ceramic Wall Tile
 - 10.5mm Thickness
 - Matte Finish
 - Pressed Edge
 - **V1** - Uniform Appearance
 - Frost Resistance = No



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.

- Product Info:**
- Porcelain Tile
 - 10.5mm Thickness
 - Matte Finish
 - Rectified Edge
 - PEI Rating = 4
 - **V2** - Slight Shading Variation
 - Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com