


| Features  | Test Method      | Value                 |
|---|------------------|-----------------------|
| Length and Width  | ISO 10545-2      | ±2.0 mm               |
| Thickness   |                  | ±0.5 mm               |
| Straightness of Sides   |                  | Compliant             |
| Rectangularity  |                  | ±1.5 mm               |
| Surface Flatness  |                  | Compliant             |
| Surface Quality   |                  | Compliant             |
| Warpage   |                  | ±2.0 mm               |
| Wedging   |                  | ±2.0 mm               |
| Water Absorption  |                  | Eb < 0.5%             |
| Modulus of Rupture / Bending Strength   |                  | ISO 10545-3           |
| Breaking Strength   | ISO 10545-4      | ≥ 1300 N              |
| Surface Hardness (Mohs)   | UNI EN - 101     | 7                     |
| Resistance to Surface Abrasion  | ISO 10545-6      | < 150 MM <sup>3</sup> |
| Coefficient of Linear Thermal Expansion   | ISO 10545-8      | < 9MK-1               |
| Thermal Shock Resistance  | ISO 10545-9      | Resistant             |
| Frost Resistance  | ISO 10545-12     | Resistant             |
| Chemical Resistance (Domestic)  | ISO 10545-13     | UA                    |
| Chemical Resistance (Low Concentration)   |                  | ULA-ULB               |
| Chemical Resistance (High Concentration)  |                  | UHA-UHB               |
| Stain Resistance  | ISO 10545-14     | Class 5               |
| Slip Resistance   | ANSI A326.3:2021 | DCOF = 0.52           |
| Recycled Content  | -                | ≥20%                  |
|  <p>This product will contribute to USGBC registered LEED projects.<br/>           It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.<br/>           Low Emissions Material • Zero VOC</p> |                  |                       |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes

