


Features	Test Method	Value
Length and Width	ASTM C499	0.38
Thickness		9mm (max ± 0.030 inch)
Warpage	ASTM C485	Conforms
Water Absorption	AST C373	≤0.5%
Breaking Strength	ASTM C648	≥ 450 lbf
Surface Hardness (Mohs)	EN 101	7 MOHS
Coefficient of Linear Thermal Expansion	ASTM C372	Conforms
Thermal Shock Resistance	ASTM C484	Conforms
Chemical Resistance (Domestic)	ASTM C650	Conforms
Chemical Resistance (Low Concentration)		Conforms
Chemical Resistance (High Concentration)		Conforms
Stain Resistance	ASTM C1378	Conforms
Slip Resistance	ANSI A137.1	DCOF 0.73
Recycled Content	-	40%







This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com