

Features	Test Method	Value
Length and Width	ISO 10545-2	Conforms
Thickness		9mm
Straightness of Sides		Rectified
Surface Flatness		Compliant
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ISO 10545-3	≤ 0.1%
Modulus of Rupture / Bending Strength	ISO 10545-4	54.6
Breaking Strength	ISO 10545-4	2094
Abrasion Resistance	ISO 10545-6	Conforms
Coefficient of Linear Thermal Expansion	ISO 10545-8	~ 7 (10 <sup>-6</sup> °C <sup>-1</sup> )
Thermal Shock Resistance	ISO 10545-9	Resistant
Expansion in Humidity	ISO 10545-10	≤ 0.1 (mm/m)
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance (Low Concentration)	ISO 10545-13	Resistant
Stain Resistance	ISO 10545-14	Cleanable
D.C.O.F. (WET) Slip Resistance	ANSI A326.3	0.69
Recycled Material	-	Cloud   Jade   Iron   Dark = 20%
VOC Emissions	-	Low Emissions Material - Zero VOC

This product will contribute to USGBC registered LEED projects.  
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Porcelain Tile
- Matte Finish
- 6mm | 9mm | 20mm Thicknesses
- Rectified Edge
- V2 - Moderate Variation
- Frost Resistance = Yes

