

| Features | Test Method | Fixed Value |
|---|--------------|--------------------------------------|
| Length And Width | ISO 10545-2 | ± 0.6% (± 2.00 mm) |
| Thickness | | ± 5% (± 0.5 mm) |
| Warpages Of Edges | | ± 0.5% (± 1.5 mm) |
| Wedging | | ± 0.5% (± 2.00 mm) |
| Flatness | | ± 0.5% (± 2.00 mm) |
| Water Absorption | ISO 10545-3 | ≤ 0.5% |
| Bending Strength | ISO 10545-4 | ≥ 35 N/ mm ² |
| Breaking Strength | | > 1300 N |
| Coefficient of Linear Thermal Expansion | ISO 10545-8 | ≈ 7X10 ⁻⁶ C ⁻¹ |
| Thermal Shock Resistance | ISO 10545-9 | Resistant |
| Frost Resistance | ISO 10545-12 | Resistant |
| Resistance of Chemical Attack | ISO 10545-13 | Resistant |
| Stain Resistance | ISO 10545-14 | Class 3 |
| Colors Resistance to Light | DIN 51094 | No Alteration |
| Slip Resistance (DCOF) | ANSI 137.1 | 0.54 |
| Recycled Content | - | ≥ 10 |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 9.5 mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- PEI Rating 5
- Frost Resistance = Yes

