

Features	Test Method	Value			
		Soft Matte		Structured	
Thickness	ISO 10545-2	6mm - 9mm		20mm	
Water Absorption	ISO 10545-3	≤ 0.1%			
Bending Strength	ISO 10545-4	Conforms		N/A	
Breaking Strength		Sps ≥ 7.5 mm S ≥ 1300 N		> 10,000 N	
Abrasion Resistance	ISO 10545-6	Conforms			
Coefficient of Linear Thermal Expansion	ISO 10545-8	> 7 (10-6 °C-1)			
Thermal Shock Resistance	ISO 10545-9	Resistant			
Expansion in Humidity	ISO 10545-10	≤ 0.1 (mm/m)			
Frost Resistance	ISO 10545-12	Resistant			
Chemical Resistance (Domestic)	ISO 10545-13	A			
Chemical Resistance (Low Concentration)		LA			
Chemical Resistance (High Concentration)		HA			
Stain Resistance	ISO 10545-14	Class 5			
Slip Resistance	ANSI A326.3	DCOF	Soft 0.43	Matte 0.74	Structured 0.80
Recycled Content	-	20% Excludes Candle, Glare and Decos			
Declare	-	Red List Free			
VOC Emissions	-	Zero VOC			



This product will contribute to USGBC registered LEED projects. It also conforms with ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Wall Deco Installation Instructions: When laying the material it is recommended not to use mechanical leveling systems, which could cause damage to the surface when removed. Before grouting wall decos, it is advised to protect the surface in the parts near the edge with masking tape. Cement-based, not epoxy-based, grouts must be used. Immediately after grouting, remove any residues with water and a soft cloth, without using abrasive sponges.

Cleaning and Maintenance Wall Decos: For ordinary cleaning, avoid abrasive products that could damage the surface. Cleaning with a soft cloth and neutral PH products is recommended to avoid dulling or scratching.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Rectified Edge
- Matte | Soft | Structured Finishes
- V2 - Slight Shading Variation
- 6mm | 9mm | 20mm Thicknesses
- Frost Resistance = Yes



www.genrose.com